

Stride™ P Dura Driven by Tempus


T Stride P Dura Pro, T Stride P Dura 800, T Stride P Dura 700,
T Stride P Dura 600, T Stride P Dura 500
13 BTE hearing aid series



Stride P Dura

SoundCore		T Pro	T 800	T 700	T 600	T 500
SoundNav	Music	•	•			
	Noise	•	•	•		
	Conversation in a crowd	•	•	•		
	Conversation in a small group	•	•	•		
	Conversation in quiet	•	•	•	•	
	Conversation in noise	•	•	•	•	
	Quiet	•	•	•	•	
	Total environments	7	7	6	3	AutoMic
SpeechPro	SpeechPro	•	SpeechZone2	SpeechZone		
	Speech Locator	•	•	•		
	Speech Focus	•				
	Dynamic Spatial Awareness	•				
Sound Conductor	Speech enhancement	•	•	•	•	•
	Noise reduction	•	•	•	•	•
	Adaptive directionality	Multiband	Multiband	Multiband	Multiband	•
Spatial Awareness	Spatial Awareness	Dynamic	Personalized	•		
	Pinna Effect	•	•	•	•	•

Fitting guides



--- Slim tube (power dome)

Sound Stabilization

AntiShock 2	•	•	•	•	•
Wind control	•	•	•	•	•
Feedback manager	•	•	•	•	•
Natural Sound Balance	•	•	•	•	•

Experience innovations

Patient insights	Log It All	•	•	•	•	•
	Patient Ratings	•	•	•	•	•
	Data logging	•	•	•	•	•
Flex	Flex:trial	•	•	•	•	•
	Flex:upgrade		•	•	•	•

Convenience






DuoLink	•	•	•	•	•
Telecoil, easy-t and easy-DAI	•	•	•	•	•
Binaural Phone	•	•	•	•	

Fitting

Automatic Adaptation Manager	•	•	•	•	•
MyMusic	Binaural	Binaural	•	•	•
Frequency compression	•	•	•	•	•
Tinnitus masker	•	•	•	•	•
IntelliVent	•	•	•	•	•
Streaming programs	•	•	•	•	•
Manual programs	•	•	•	•	•
NAL-NL2/NL1 and DSLv5	•	•	•	•	•
Fitting channels	20	20	16	10	6

Stride P Dura is rated IP 68





ANSI 3.22 2014/IEC 60118-7 2005 2cc coupler technical data

	Reference test frequency - IEC 60118-7 (kHz)	1.6	1.6
	OSPL90		
	Maximum (dB SPL)	123	131
	HFA - OSPL90 (dB SPL)	116	122
	at RTF (dB SPL)	112	127
	Full on gain (input 50 dB SPL)		
	Maximum (dB)	55	63
	HFA - FOG (dB)	45	52
	at RTF (dB)	41	57
	Reference test setting (RTS)		
	Frequency range (Hz)	<100 - 6500	<100 - 7300
	Reference test gain (dB)	39	45
	Current drain at RTS (mA)	1.2	1.2
	Typical battery life (h)	260	260
	Equivalent input noise at RTS (dB SPL)	19	19
	Induction coil sensitivity (31.6 mA/m)		
	HFA SPLITS/STS-RSETS (dB SPL/dB)	99/0	105/0
	 <p>Standard: mic at 70 dB SPL vs induction coil at 100 mA/m</p> <p>--- Mic - - - Induction Coil</p>		

Electromagnetic compatibility

EMC immunity by ANSI c63.19-2011 EMC, omni/telecoil	M4/T4	M4/T4
---	-------	-------

IEC 60118-o OES coupler technical data

	Reference test frequency - IEC 60118-o (kHz)	1.6	1.6
	OSPL90		
	Maximum (dB SPL)	128	134
	at RTF (dB SPL)	120	134
	Full on gain (input 50 dB SPL)		
	Maximum (dB)	59	67
	at RTF (dB)	48	64
	Basic frequency response		
	Frequency range (DIN 45605) (Hz)	<100 - 6500	<100 - 8000
	Reference test gain (dB)	41	57
	Current drain at RTG (mA)	1.2	1.2
	Typical battery life (h)	260	260
	Equivalent input noise at RTG (dB SPL)	19	19
	Induction coil sensitivity		
	at RTF (graph shown for 31.6 mA/m at RTG) (dB SPL)	101	117
<p>Electromagnetic compatibility</p>	EMC immunity by IEC 60118-13, 2011 field strength	27/27/31	27/27/31
	90/50/35 V/m, omni. IRIL low/medium/high band (dB SPL)		

Legend

-  Earhook
-  Slim Tube

Test conditions

Earhook: filtered; Battery size: 13; Source: voltage 1.3 V; Tubing: length 25 mm, inside diameter 1.93 mm
 The hearing instrument is set to Unitron Truefit test settings. LLE is applied at an approximate level of 35 dB SPL.
 Domes should never be fit on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend use of a customized earmold.
 Sound pressure level of these hearing aids exceeds 132 dB SPL.
 We reserve the right to change specification data without notice as improvements are introduced.